

Applicants: Rles et al.
Serial No. 10/632,058
Page 5

IN THE CLAIMS:

1. (Currently Amended) A connector assembly for detachably connecting a lead to an implantable medical device, comprising:

a first deflectable connector clip including a first arm, a second arm, and a top portion extending between the first arm and the second arm; and

a housing having a first member and a second member, the first member having a first outer surface forming an annular shelf and the second member having a second outer surface and a cylindrical rim extending outward along and perpendicular to an outer edge of the second outer surface, the annular shelf of the first member formed to received the cylindrical rim to be fixedly engaged with the second member to retain the first connector clip within the housing, and at least one of the first member and the second member including the engaged first member and the second member forming an aperture for receiving the lead;

a first inner surface of the first member extending from the aperture to the first outer surface and a second inner surface of the second member extending from the aperture to the second outer surface;

a first deflection portion extending outward from at least one of the first inner surface and the second inner surface along the top portion of the first deflectable clip; and

a second deflection portion extending outward from the at least one of the first inner surface and the second inner surface to be positioned between the first arm and the second arm, the second deflection portion deflecting the connector clip from a first position corresponding to a first distance between the first arm and the second arm, to a second position corresponding to a second distance between the first arm and the second arm.

Claim 2 (Canceled)

Applicants: Ries et al.
Serial No. 10/632,058
Page 6

3. (Original) The connector assembly of claim 1, wherein the housing and the connector clip are formed of an electrically conductive metal.
4. (Original) The connector assembly of claim 3, wherein the electrically conductive metal is stainless steel.
5. (Currently Amended) The connector assembly of claim 1, wherein ~~the first member and the second member form an aperture to receive the lead, and the~~ first arm and the second arm are ~~engage~~ engaged against the lead as the lead is advanced through the aperture to further deflect the first arm and the second arm from the second position to a third position.
6. (Currently Amended) The connector assembly of claim 5, wherein the second deflection portion extends between a first end and a second end, and the first arm and the second arm are engaged against the first end and the second end, respectively, when the connector clip is in the second position.
7. (Original) The connector assembly of claim 6, wherein the first arm and the second arm extend a distance outward from the first end and the second end, respectively, when the connector clip is in the third position.
8. (Currently Amended) The connector assembly of claim 1, further comprising:
a second deflectable connector clip, ~~wherein the other of the first member and the second member includes a second deflection portion~~ including a first arm, a second arm arm, and a top portion extending between the first arm and the second arm of the second connector clip;

Applicants: Ries et al.
Serial No. 10/632,058
Page 7

a third deflection portion extending outward from the other of the first inner surface and the second inner surface along the top portion of the second connector clip; and

a fourth deflection portion, extending outward from the other of the first inner surface and the second inner surface to be positioned between the first arm and the second arm of the second connector clip, deflecting the second connector clip from the first position to the second position.

9. (Original) The connector assembly of claim 8, wherein the first connector clip is positioned generally perpendicular to the second connector clip.

Claim 10 (Canceled)

11. (Currently Amended) The connector assembly of claim 8, wherein ~~the first member and the second member form an aperture to receive the lead, and the~~ first arm and the second arm of the first connector clip and the first arm and the second arm of the second connector clip are engage against the lead as the lead is advanced through the aperture to further deflect the first arm and the second arm of the first connector clip and the first arm and the second arm of the second connector clip from the second position to a third position.

12. (Currently Amended) The connector assembly of claim 10, wherein the first arm and the second arm of the first connector clip are positioned outward from the first second deflection portion and the first arm and the second arm of the second connector clip are positioned outward from the ~~second~~ fourth deflection portion when the first connector clip and the second connector clip are in the third position.

Claim 13 (Canceled)

Applicants: Ries et al.
Serial No. 10/632,058
Page 8

14. (Currently Amended) The connector assembly of claim 1, wherein ends of the first arm and the second arm include tapered portions to provide clearance between the ends and the housing.

15. (Currently Amended) An implantable medical device capable of being detachably connected to a lead, comprising:

a first deflectable connector clip including a first arm, a second arm, and a top portion extending between the first arm and the second arm; and

a housing having a first member and a second member, the first member having a first outer surface forming an annular shelf and the second member having a second outer surface and a cylindrical rim extending outward along and perpendicular to an outer edge of the second outer surface, the annular shelf of the first member formed to received the cylindrical rim to be fixedly engaged with the second member to retain the first connector clip within the housing, and at least one of the first member and the second member including the engaged first member and the second member forming an aperture for receiving the lead;

a first inner surface of the first member extending from the aperture to the first outer surface and a second inner surface of the second member extending from the aperture to the second outer surface;

a first deflection portion extending outward from at least one of the first inner surface and the second inner surface along the top portion of the first deflectable clip; and

a second deflection portion extending outward from the at least one of the first inner surface and the second inner surface to be positioned between the first arm and the second arm, the second deflection portion deflecting the connector clip from a first position corresponding to a first distance between the first arm and the second arm, to a second position corresponding to a second distance between the first arm and the second arm.

Claim 16 (Canceled)

Applicants: Ries et al.
Serial No. 10/632,058
Page 9

17. (Original) The device of claim 15, wherein the housing and the connector clip are formed of an electrically conductive metal.
18. (Original) The device of claim 17, wherein the electrically conductive metal is stainless steel.
19. (Currently Amended) The device of claim 15, wherein ~~the first member and the second member form an aperture to receive the lead, and~~ the first arm and the second arm are engage against the lead as the lead is advanced through the aperture to further deflect the first arm and the second arm from the second position to a third position.
20. (Currently Amended) The device of claim 19, wherein the second deflection portion extends between a first end and a second end, and the first arm and the second arm are engaged against the first end and the second end, respectively, when the connector clip is in the second position.
21. (Original) The device of claim 20, wherein the first arm and the second arm extend a distance outward from the first end and the second end, respectively, when the connector clip is in the third position.
22. (Currently Amended) The device of claim 15, further comprising:
a second deflectable connector clip, ~~wherein the other of the first member and the second member includes a second deflection portion~~ including a first arm, a second arm, and a top portion extending between the first arm and the second arm of the second connector clip;
a third deflection portion extending outward from the other of the first inner surface and the second inner surface along the top portion of the second connector clip; and

Applicants: Ries et al.
Serial No. 10/632,058
Page 10

a fourth deflection portion, extending outward from the other of the first inner surface and the second inner surface to be positioned between the first arm and the second arm of the second connector clip, deflecting the second connector clip from the first position to the second position.

23. (Original) The device of claim 22, wherein the first connector clip is positioned generally perpendicular to the second connector clip.

Claim 24 (Canceled)

25. (Currently Amended) The device of claim 22, wherein ~~the first member and the second member form an aperture to receive the lead,~~ and the first arm and the second arm of the first connector clip and the first arm and the second arm of the second connector clip are engage against the lead as the lead is advanced through the aperture to further deflect the first arm and the second arm of the first connector clip and the first arm and the second arm of the second connector clip from the second position to a third position.

26. (Currently Amended) The device of claim 24, wherein the first arm and the second arm of the first connector clip are positioned outward from the ~~first~~ second deflection portion and the first arm and the second arm of the second connector clip are positioned outward from the ~~second~~ fourth deflection portion when the first connector clip and the second connector clip are in the third position.

Claim 27 (Canceled)

28. (Currently Amended) The device of claim 15, wherein ends of the first arm and the second arm include tapered portions to provide clearance between the ends and the housing.